




LITHIUM IRON PHOSPHATE BATTERY

FEATURES Lithium Iron Phosphate (LiFePO4): the Safest Lithium Technology.
 Integrated Battery Management System(BMS).
 Bluetooth/RS485/RS232/SMBus/CANBus (Optional).
 SOC LED/LCD Indicator(Optional).

PERFORMANCE Long Cycle Life > 2000cycles @ 100% DOD.
 High Density, High Discharge Current, High Temperature Range.
 Low Weight, Free Maintenance.
 Fast Charging.
 Environment Friendly.



MIL48-5,12(51.2V100Ah, 5120Wh)

BATTERY DATA SHEET

Electrical Parameters

Nominal Voltage	51.2V
Rated Capacity	100Ah
Energy	5120Wh
Resistance	≤30m Ω
Efficiency	99%
Cycle Life	>2000cycles @1C, 100% DOD
Self Discharge	2% per Month
Max. Modules in Series/Parallel	16S/1P

Mechanical Parameters

Dimension(L x W x H)	600x340x230 mm 23.62x13.38x9.05"
Weight	65kg(143.3lbs)
Terminal Type	M8
Battery Housing	METAL, UL-94 V-0
Housing Protection	IP65
Cell Type-Chemistry	LiFePO4
SOC Display(Optional)	LED/LCD Indicator

Discharge Parameters

Continuous Discharge Current	200A
Pulse Discharge Current	600A(>3seconds)
Recommended Volt. Disconnect	40V
BMS Discharge Cut-off Voltage	32V
Reconnect Voltage	36.8V
Short Circuit Protection	200~600 us

Charge Parameters

Charge Method	CC-CV
Charge Voltage	58.4V
Recommended Float Voltage	55.2V
Recommended Charge Current	50A
Maximum Charge Current	100A
BMS Charge Cut-off Voltage	62.4V

Compliance Certificate

Certifications	UL1642(cell)
	CE
	IEC62133 & CB
	KC
	BIS
Shipping Classification	UN3480, Class 9, UN38.3


Temperature Parameters

Discharge Temperature	-30 to 60°C (-22 to 140°F)
Charge Temperature	0 to 45°C (32 to 113°F)
Storage Temperature	-40 to 60°C(-40 to 140°F)
BMS High Temperature Cut-off	80°C(176°F)




Performance Characteristics


CYCLE LIFE vs. DEPTH OF DISCHARGE(DOD)
DISCHARGE@1C, 25°C




DISCHARGE CAPACITY at VARIOUS TEMPERATURES
DISCHARGE @1C, 25°C




STATE OF CHARGE CURVE @1C, 25°C




CHARGING CHARACTERISTICS @1C, 25°C



Battery Dimension



M8 - 1.0x 8mm
Threaded Hole



Battery Recycle



Battery Applications

- + Data Center UPS
- + Telecom Backup Power
- + Military Power Supply
- + Solar Energy Storage System
- + Solar Street LED Lightings
- + Autonomously Guided Vehicles (AGVs)
- + Industrial Robotics & Handling Equipment
- + Aerial Work Platform
- + Floor Cleaning Machines
- + Power Tools, Lawn Mower
- + Electric Bike & Motorcycles
- + Electric Mobilities(E-scooters, Wheelchair)
- + Golf Trolley & Golf Carts
- + Medical Devices
- + Electric Ships
- + Passenger Vehicles

NOTE: Do Not Mix With Sealed Lead Acid Batteries When Recycling.
See User's Manual for Proper Operation.